

PINZE POTB L

I - Pinza tronchi a cilindro orizzontale senza lama - Serie leggera

GB - Log grab with horizontal cylinder without blade - Light version


D - Holzgreifer mit liegendem Zylinder ohne Klinge - Leichte Ausführung

F - Pince à bois à vérin horizontal sans lame - Série légère

E - Pinza para manipulación de troncos con cilindro horizontal sin lámina - Serie ligera



DISEGNO TECNICO / TECHNICAL DRAWING



Portata gru a braccio sfilato / Lifting capacity at the end of boom



Peso escavatore / Excavator weight

Modello Type	Capacità Capacity	Portata Load	Peso Weight	Pressione Pressure	Portata olio Oil flow	Ton.	Ton.	A	B	C	D	E	F	L
	M ²	kg	kg	Max bar	Lt/min			mm	mm	mm	mm	mm	mm	mm
POTB 80 L	0,08	500	39	180	10	0,1-0,3	1,0-1,5	480	790	520	375	330	50	200
POTB 100 L	0,15	800	65	180	25	0,2-0,5	1,5-2,0	680	1000	680	450	435	55	250
POTB 250 L	0,20	1500	115	180	30	0,3-0,7	2,0-3,0	720	1300	660	510	510	60	350
POTB 350 L	0,30	2500	170	180	40	0,5-1,0	3,0-5,0	800	1470	750	570	575	67	450
POTB 450 L	0,40	3000	260	180	50	0,8-1,6	5,0-8,0	945	1740	880	690	690	95	550

KIT DENTI PER POTB L


I - Kit denti amovibili

GB - Kit removable teeth


D - Kit abnehmbaren Zähnen

F - Kit dents amovibles

E - Kit dientes amovibles



DISEGNO TECNICO / TECHNICAL DRAWING



Portata gru a braccio sfilato / Lifting capacity at the end of boom




Peso escavatore / Excavator weight

Modello Type	Capacità Capacity	Portata Load	Peso Weight	Pressione Pressure	Portata olio Oil flow	Ton.	Ton.	A	B	C	D	E	F	L
	M²	kg	kg	Max bar	Lt/min			mm	mm	mm	mm	mm	mm	mm
KD-POTB 80 L	0,08	500	59	180	10	0,1-0,3	1,0-1,5	465	790	520	500	330	206	448
KD-POTB 100 L	0,15	800	105	180	25	0,2-0,5	1,5-2,0	570	1000	680	665	435	310	650
KD-POTB 250 L	0,20	1500	170	180	30	0,3-0,7	2,0-3,0	680	1300	660	725	510	330	750
KD-POTB 350 L	0,30	2500	250	180	40	0,5-1,0	3,0-5,0	765	1470	750	800	575	360	910
KD-POTB 450 L	0,40	3000	370	180	50	0,8-1,6	5,0-8,0	910	1740	880	945	690	430	1010


KIT BENNA PER POTB L

I - Kit pareti benna amovibili

- GB - Kit removable side-walls
- D - Kit abnehmbaren Seitenschalen
- F - Kit parois amovibles
- E - Kit paredes laterales amovibles



DISEGNO TECNICO / TECHNICAL DRAWING



Portata gru a braccio sfilato / Lifting capacity at the end of boom



Peso escavatore / Excavator weight

Modello Type	Capacità Capacity Lt	Portata Load kg	Peso Weight kg	Pressione Pressure Max bar	Portata olio Oil flow Lt/min	 Ton.	 Ton.	A mm	B mm	C mm	D mm	L mm
KB-POTB 80 L	70	500	81	180	10	0,1-0,3	1,0-1,5	660	854	545	585	448
KB-POTB 100 L	160	800	143	180	25	0,2-0,5	1,5-2,0	835	1000	700	740	650
KB-POTB 250 L	240	1500	215	180	30	0,3-0,7	2,0-3,0	960	1450	690	830	750
KB-POTB 350 L	370	2500	310	180	40	0,5-1,0	3,0-5,0	1080	1640	785	940	910
KB-POTB 450 L	550	3000	440	180	50	0,8-1,6	5,0-8,0	1240	1920	910	1100	1010