FORMIKO HYDRAULICS

ROTATOR FHR 3LH

30 kN

15 kN

900 nm

18 kg

20 l/min

L60 ø25	R	R	GO/GC	GO	GC
mm	3/8" BSP	250 bar	3/8" BSP	200 bar	300 bar

Rotator's upper mount is applied in EYE form factor of the knuckle joint. Robust and tough built to withstand even overloads. The wide of eye is common standard width 60mm and the knuckle pin diameter 25mm.



Hydraulic rotator FHR 3LH is cost-effective solution generally for seasonal use in forestry, agriculture, road and building construction, general cargo and material handling.



FHL 01-A/B-60/25



FHL 01B-A/B-60/25



FHL 05B-A/B-60/25




FHL 05-A/B-60/25





FHL 04-2525

Rotator lower mount is applied in AXLE form factor to mount in grapple / tool mounting tube or addaptor and by fixing with pin. Axle (shaft) diameter is 49.5mm and the fixing pin (not included) diameter 25mm

ø49.5 ø25	GO/GC
mm	3/8" BSP







For additional information relating to price levels and technical data, please contact sales@formiko.lv

Formiko Hydraulics Ltd
Dzirciema Str. 119 k-1,
Riga LV1055 LATVIA

+371 294 49 552
+371 264 59 383
sales@formiko.lv
www.formiko.lv

On request by special conditions there are metric nipples available for rotator FHR 3LH

FORESTRY AGRICULTURE CONSTRUCTION

Current document is automatic generated at www.formiko.lv on 08/03/2026.
Please always make sure that it's up to date and try to be paperless!

FORMIKO HYDRAULICS

ROTATOR FHR 3LH

Hydraulic rotator FHR 3LH is cost-effective solution generally for seasonal use in forestry, agriculture, road and building construction, general cargo and material handling.

Rotator's upper mount is applied in EYE form factor of the knuckle joint. Robust and tough built to withstand even overloads. The wide of eye is common standard width 60mm and the knuckle pin diameter 25mm.

Rotator lower mount is applied in AXLE form factor to mount in grapple / tool mounting tube or addaptor and by fixing with pin. Axle (shaft) diameter is 49.5mm and the fixing pin (not included) diameter 25mm

Rotator FHR 3LH based on reliable vane type hydraulic motor which delivers torque up to 900Nm at 25MPa.

Formoko rotator FHR 3LH is compatible with FHL 01-A/B-60/25 and FHL 01B-A/B-60/25 and FHL 05B-A/B-60/25 and FHL 05-A/B-60/25 and FHL 04-2525 series links.

Rotator for shipping is packed in compact solid cardboard box with dimensions 340x230x240mm.

We providing TWO year warranty for this rotator.

For additional information relating to price levels and technical data, please contact sales@formiko.lv

Formiko Hydraulics Ltd
Dzirciema Str. 119 k-1,
Riga LV1055 LATVIA

+371 294 49 552
+371 264 59 383
sales@formiko.lv
www.formiko.lv

On request by special conditions there are metric nipples available for rotator FHR 3LH

FORESTRY AGRICULTURE CONSTRUCTION

Current document is automatic generated at www.formiko.lv on 08/03/2026.
Please always make sure that it's up to date and try to be paperless!